

Patch fitting set, self closing, with side panel pivot and floor spring for double action doors in glass wall



- > For glass thickness 10-12 mm
- > Max load bearing capacity 80 kg
- > Max door width 950 mm
- > For left and right hand use
- > Matt stainless steel
- > Set includes:
 - A Startec bottom patch fitting, concealed clamp fixing with hexagon socket head screws and adapter plate for 10 mm thick glass included with insert for flat conical floor spring pivot
 - B Startec top patch fitting, concealed clamp fixing with hexagon socket head screws and adapter plate for 10 mm thick glass included with plastic pivot insert for bolt Ø 15 mm
 - F Startec fanlight/side panel pivot patch fitting, counter bearing for to patch fitting, concealed clamp fixing with hexagon socket head screws, bolt can be adjusted laterally by +/- 3 mm, adapter plate for 10 mm thick glass included
 - M Startec floor spring. DoP No.: 932.84.A. Closing force size 3. Maximum opening angle 130°. Comes complete with cover plate and double action pivot set. Replaceable spindle insert, with top centre set. CE marked. Tested in accordance with BS EN 1154:1997
- > Order qty: 1 pc



Full product details for patch fittings are shown on pages **10-13**
Full product details for floor spring is shown in **Section 4 page 42**

For double action doors	
A Startec bottom patch fitting	1 pc
B Startec top patch fitting	1 pc
F Startec fanlight/side panel pivot patch fitting	1 pc
M Startec floor spring	1 pc
Cat. No.	981.00.913