

Naber PRIME Flow P-RBV 150 pipe bend 90°



System 150

- > N-click system with integrated latching elements
- > N-Klick system for secure connection with the universal connector
- > With optimised guide vanes
- > Improved flow technology
- > Light grey
- > Order qty: 1 pc

System	Width x height	Cat. No.
150	226 x 226 mm	500.97.084

Naber PRIME Flow base ventilation grid flow



Matt black



Stainless steel

- > Slatted ventilation grid made of anodised aluminium profiles
- > For ducted downdraft or hob ventilation systems with integrated activated carbon filters in recirculation mode
- > Suitable for base heights of 100-150 mm (can be shortened)
- > For connection to COMPAIR® flow flat duct pipe or GREENflow Flex duct
- > Ventilation shaft: 210 cm²
- > Cut-out dimensions (H x W): 150 x 282 mm
- > Cover dimensions (H x W): 150 x 297 mm
- > Connector dimensions: 89 x 222 mm
- > Connector depth: 45 mm
- > Light grey
- > Order qty: 1 pc

System	Finish	Cat. No.
150	Matt black	500.97.086
150	Stainless steel	500.97.087

TCH DESIGN 2020. © Häfele U.K. Ltd 2020. Dimensional data not binding. We reserve the right to alter specifications without notice.