

Sealing tape



- > 50 mm x 10 m
- > Flame retardant
- > Order qty: 1 pc

	Cat. No.
Sealing tape	565.30.890

Flexible ducting hose, aluminium



- > Flame resistant properties of aluminium combine with the strength of polyester making this the ideal hose for cooker hood installation
- > Will prevent the spread of flames in cabinets
- > Fits threaded hose connectors
- > Polyester reinforced aluminium hose
- > Length: 1 m
- > Order qty: 1 pc

Internal dimensions	Cat. No.
Ø 100 mm	565.30.810
Ø 125 mm	565.30.812

Rectangular flexible ducting hose, white PVC



- > In a rectangular configuration to assist fitting at awkward angles or levels
- > Will connect to flat duct but must be securely attached with sealing tape
- > Flame retardant white PVC
- > Length: 3 m
- > Order qty: 1 pc

Internal dimensions	Cat. No.
110 x 54 mm	565.30.791
204 x 60 mm	565.30.793
220 x 90 mm	565.30.795

Elbow 90° bend, grey PVC



Male



Female

- > Elbow 90° bend ducting adaptor for joining round pipe, flexible hose and flat channel ducting
- > Male connector will slot inside the ducting, female connector will slot around ducting, where male / female type is stated
- > For mechanical ventilation purposes, also connects flat duct to cooker hood outlet
- > Flame retardant grey PVC
- > Order qty: 1 pc

Flat duct dims	Aperture Ø	Type	Cat. No.
110 x 54 mm	100	Female	565.30.820
110 x 54 mm	100	Male	565.30.824
204 x 60 mm	125	-	565.30.822
220 x 90 mm	150	-	565.30.823
204 x 60 mm	150	-	565.30.625