



Häfele Dresscode pull out frame




B = frame width including runners

Installation dimensions



Drilling pattern



Hook-in shelf dimensions for self-manufacture

Depth	For cabinet width	Hook-in shelf width with side panel thickness		
		16 mm	19 mm	25 mm
466 mm	500 mm	311 mm	305 mm	293 mm
	600 mm	411 mm	405 mm	393 mm
	800 mm	611 mm	605 mm	593 mm
	900 mm	711 mm	705 mm	693 mm
	1000 mm	811 mm	805 mm	793 mm

- > Can be freely positioned at intervals of 32 mm
- > Easy installation and disassembly without tools
- > The system can be adapted to customer requirements at any time
- > Individual configuration with hook-in elements
- > Area of application: Pull out frame for individual configuration with hook-in elements such as boxes, shoe rack, laundry bag, cosmetic insert, jewellery insert or hook-in shelf. The pull out frame can also be clad on the front with a designer panel or wooden panel (optional)
- > Type of pull out: Full extension with self closing and soft closing mechanisms
- > Version: Cross profile can be cut to required size
- > Internal installation depth: Min. 520 mm
- > Installation height: Max. 900 mm
- > Nom. length: 500 mm
- > Load bearing capacity: Max. 15 kg
- > Frame installation: For plug fitting without tools
- > Runners installation: For mounting in provided series drilled holes (wooden cabinet) or on strut (aluminium frame system) without tools
- > Powder coated steel and aluminium frame, plastic joint set
- > Set includes:
 - 2x end sections with joints
 - 2x cross profiles
 - 1x pair of runners with Häfele Dresscode connector
- > Order qty: 1 pc



> Order reference:

Cabinet width = 2 x side panel thickness + frame width B + spacer bars (42 mm)

- > Spacer bars are mandatory in order to compensate for the door offset in the cabinet. Please order separately, shown on page 2.17

Width B	For cabinet width	Umber grey RAL 7022	Traffic white RAL 9016
For side panel thickness 16 mm			
426 mm	500 mm	806.34.502	806.34.702
526 mm	600 mm	806.34.503	806.34.703
726 mm	800 mm	806.34.504	806.34.704
826 mm	900 mm	806.34.505	806.34.705
926 mm	1000 mm	806.34.506	806.34.706
For side panel thickness 19 mm			
420 mm	500 mm	806.34.512	806.34.712
520 mm	600 mm	806.34.513	806.34.713
720 mm	800 mm	806.34.514	806.34.714
820 mm	900 mm	806.34.515	806.34.715
920 mm	1000 mm	806.34.516	806.34.716
For side panel thickness 25 mm			
408 mm	500 mm	806.34.522	806.34.722
508 mm	600 mm	806.34.523	806.34.723
708 mm	800 mm	806.34.524	806.34.724
808 mm	900 mm	806.34.525	806.34.725
908 mm	1000 mm	806.34.526	806.34.726



Most of the products you will find in this Directory are available within 24 hours. However, to be able to offer the breadth of range in our collection, a small number of products have a longer lead time that is typically around 14 days. Please call 0800 171 2909 for an accurate delivery date when you see this symbol.