

LOOX5 12V LED 2025 DOWNLIGHT, MODULAR, Ø 65 MM


These lights can be used in a variety of different applications thanks to the modular principle with optional bezels for either surface or recess mounting. Snap-in lead gives a connection that is secure but also allows the light to be easily released.



5

Lighting: Loox5 LED

Loox5 12V LED 2025 downlight, Ø 65 mm



Modular design -

Round or square, surface or recess mounting bezels.
For use with leads with snap-in connector.

- > For recess mounting, press-fit in Ø 58 mm hole, order bezel separately
2.6 mm rim, min. 13.5 mm hole depth required
- > For surface mounting, order bezel separately
- > Voltage: 12V. Wattage: 3.8W
- > Dimmable
- > Degree of protection:
IP44 as recess mounted downlight
IP20 as surface mounted downlight
- > Lead not included, must be ordered separately
- > Silver coloured aluminium housing
- > Order qty: 1 pc

Distance	LED 2025			
	2700 K	3000 K	4000 K	5000 K
250 mm	2600 Lx	2650 Lx	2700 Lx	2800 Lx
500 mm	730 Lx	750 Lx	780 Lx	800 Lx
750 mm	320 Lx	350 Lx	345 Lx	350 Lx
1000 mm	180 Lx	185 Lx	185 Lx	190 Lx

Output:	2700 K	3000 K	4000 K	5000 K
Light colour:	Warm white		Cool white	
Wattage (W/m):	3.8	3.8	3.8	3.8
Energy efficiency:	A+ G	A+ F	A+ F	A+ F
Number of diodes	1 (COB)	1 (COB)	1 (COB)	1 (COB)
Light output (Lm):	270	300	306	345
Efficacy (Lm/W):	71	78	80	90
Colour Rendering Index:	>90	>90	>90	>83



- > For recess or surface mounting order bezels separately, shown on page 5.107
- > Order lead with snap-in connector separately, shown on page 5.107

5 12V



Output	2700 K	3000 K	4000 K	5000 K
Cat. No.	833.72.350	833.72.351	833.72.352	833.72.323

YOU ALSO NEED:



DRIVER
Page 5.156



LEAD
Page 5.107



SWITCH
Page 5.160-166

OPTIONAL ACCESSORIES
Pages 5.158-159, 5.167-168, 5.178-181

PAGE AMENDED
10.05.22/1