

LOOX5 12V LED 2090 DOWNLIGHT, MODULAR, Ø 32.5 MM

Modular downlight - order from choice of four bezel designs in three finishes for surface mounting, or recess mounting in a Ø 26 mm hole. Downlight includes Samsung LEDs and has a narrow beam angle for staging objects.



Loox5 12V LED 2090 downlight, Ø 32.5 mm

Lighting: Loox5 LED

5



Modular design -

Round or square, surface or recess mounting bezels.
Lead included

- > Equipped with high quality Samsung LEDs
- > With narrow beam angle for staging objects
- > For recess mounting, press-fit in Ø 26 mm hole, order bezel separately
1.7 mm rim, min. 11 mm hole depth required
- > For surface mounting, order bezel separately
- > Voltage: 12V. Wattage: 1.2W
- > Dimmable
- > Degree of protection:
IP44 as recess mounted downlight
IP20 as surface mounted downlight
- > With 2.0 m lead with Loox5 12V connector
- > Silver coloured aluminium housing
- > Order qty: 1 pc

Distance	55°	2700 K	3000 K	4000 K	5000 K
250 mm		930 Lx	990 Lx	1005 Lx	1005 Lx
500 mm		230 Lx	240 Lx	250 Lx	260 Lx
750 mm		95 Lx	100 Lx	110 Lx	115 Lx
1000 mm		50 Lx	55 Lx	60 Lx	60 Lx

Output:	2700 K	3000 K	4000 K	5000 K
Light colour:	Warm white		Cool white	
Wattage (W/m):	1.2	1.2	1.2	1.2
Energy efficiency:				
Number of diodes	1	1	1	1
Light output (Lm):	80	90	95	100
Efficacy (Lm/W):	67	75	79	83
Colour Rendering Index:	>90/>60	>90/>60	>90/>60	>90/>60



For recess or surface mounting order bezel separately, shown on page 5.111

5 12V



Output	2700 k	3000 K	4000 K	5000 K
Cat. No.	833.72.470	833.72.471	833.72.472	833.72.473

YOU ALSO NEED:



DRIVER
Page 5.156



SWITCH
Page 5.160-166

OPTIONAL ACCESSORIES

Pages 5.158-159, 5.167-168, 5.178-181

PAGE AMENDED
10.05.22/1