

## LOOX5 24V LED 3081 DOWNLIGHT


Create decorative effects with the LED 3081 RGB downlight by mixing any combination of light colours. The lights are controlled using the Häfele Connect Mesh system which must be ordered separately.



5

Lighting: Loox5 LED

### Loox5 24V LED 3081 downlight, 65 mm



- > For surface mounting
- > Screw fixing
- > Voltage: 12V. Wattage: 0.7W
- > Colour control only via Häfele Connect Mesh 6-way distributor with RGB adapter, must be ordered separately
- > Degree of protection: IP20
- > With 2.0 m lead with Loox5 24V connector
- > Plastic housing
- > Order qty: 1 pc

EXTRA  
FLAT  
6 mm

|                           |     |
|---------------------------|-----|
| Light colour:             | RGB |
| Number of diodes:         | 6   |
| Luminous flux (Lm):       | 20  |
| Wattage (W):              | 0.7 |
| Luminous efficacy (Lm/W): | 29  |



Control using Häfele Connect Mesh system, shown from page 5.178

|                 |            |      |     |   |         |                  |
|-----------------|------------|------|-----|---|---------|------------------|
| 5 24 V          | RGB Colour | IP20 | III | F | 7 YEARS | Fixings included |
| Finish          | RGB        |      |     |   |         |                  |
| Silver coloured | 833.77.230 |      |     |   |         |                  |

### YOU ALSO NEED:

**DRIVER**  
Page 5.157

**SWITCH**  
Page 5.160-166

**CONTROL**  
Page 5.178-180

**OPTIONAL ACCESSORIES**  
Pages 5.159, 5.167-168