

FESTOOL TS 55 FEBQ CIRCULAR SAW

With an unprecedented working speed the TS 55 now saws at up to twice the speed, with a concentrated torque and new generation cutting blades, guaranteeing perfect cutting quality with maximum cutting performance. The splinter guard and extraction system perfectly match the machine and ensure this is a top class sawing system. Available with or without guide rail.

- > For precise circular in materials up to 55 mm thick, cutting interior doors to length using guide rail and circular saw, manufacturing expansion joints in parquet flooring and false joints, cutting chipboard to size, cutting and processing plasterboard
- > Concentrated torque and up to twice as fast work progress with an increased saw blade service life
- > Virtually splinter-free on both sides thanks to attachable splinter guard
- > The cutting edge from 90° to 47° remains unchanged even when the saw swivels
- > Guide wedge for safer work and simple positioning in existing joint
- > Angle adjustment with undercut function from -1° to 47°



Festool TS 55 FEBQ circular saw



TS 55 FEBQ-Plus-FS, with guide rail



TS 55 FEBQ-Plus, without guide rail

Please note: Plug-it cable is supplied with a UK plug

 System accessories and circular saw blades, are available to order separately, see **Sections 1 and 2** of this Directory

- > Antistatic function: Mobile dust extractors and tools with the antistatic function to prevent static charge from accumulating when working
- > Splinter guard: Patented splinterguard for splinter-free cuts on both sides when sawing
- > Guide system: Patented guide system for safe guidance of saws and router bits
- > Plug it: Removable, replaceable mains cable with safety lock for quick conversion
- > MMC Multi Material Control electronics: Power electronics with constant adjustable speed and temperature monitor for work on all types of material
- > FastFix: Makes changing routing, sawing, planing, sanding, drilling and screwdriving tools easier
- > CLEANTEC: Integrated bayonet fitting as the connecting element between the extractor and the tool
- > Quick-acting brake: For safe work when planing, sawing and routing
- > **Technical data:**
 - Power consumption: 1200 W
 - Idle engine speed: 2000-5800 min-1
 - Saw blade diameter: Ø 160 mm
 - Inclination: -1 - 47°
 - Cutting depth: 0-55 mm
 - Cutting depth at 45 °: 0-43 mm
 - Dust extraction connection Ø d/e: 27/36 mm
 - Weight: 4.5 kg
- > **Supplied with:**
 - Fine cut wood saw blade HW 160 x 1.8 x 20 WD42
 - Guide rail FS 1400/2 (see table below)
 - Splinterguard
 - Flag window; vision panel
 - In a Systainer SYS3 M 337
- > Order qty: 1 set

Version / Model No.	Cat. No.
With guide rail	
TS 55 FEBQ-Plus-FS GB 240V	005.25.370
TS 55 FEBQ-Plus-FS GB 110V	000.49.219
Without guide rail	
TS 55 FEBQ-Plus GB 240V	000.49.216
TS 55 FEBQ-Plus GB 110V	000.49.218