

FESTOOL KAPEX KS 60 SLIDING COMPOUND MITRE SAW

For cutting boards and panels with sizes of up to 305 x 60 mm to length, trimming strips, profiles and timber at thicknesses of up to 60 mm and adjusting skirting boards and cover strips to precision angles quickly and precisely using the bevel.

- > Ideal for mobile use
- > Compact and lightweight, with ergonomic handles and cord holder
- > Bevel for producing interior and exterior angles
- > Inclination angle of up to 47°/46° on each side and mitre angle of up to 60° on each side



Festool KAPEX KS 60 sliding compound mitre saw, 240V



- > Antistatic function - prevents static charge from accumulating
- > MMC digital electronics - Processor controlled 'Multi Material Control' power electronics provide adjustable and constant speeds as well as temperature monitoring for work on all types of material
- > Cleantec connecting system - Integrated bayonet fitting as the connecting element between the extractor and the tool.
- > **Technical data:**
 - Power consumption: 1200 W
 - Idle engine speed: 1300-3500 RPM
 - Saw blade diameter: Ø 216 mm
 - Cutting depth 90°/90°: 305 x 60 mm
 - Cutting depth at 45°/90°: 215 x 60 mm
 - Cutting depth 45°/45° (left): 215 x 40 mm
 - Inclination angle: 47/46°
 - Mitre angle: 60/60°
 - Dimensions (W x D x H): 661 x 475 x 430 mm
 - Dust extraction connection: Ø 27/36 mm
 - Weight: 17.8 kg
- > **Supplied with:**
 - HW universal saw blade W 36
 - Clamp FSZ 120
 - Operation tool
 - In a carton
- > Order qty: 1 set

Version / Model No.	Cat. No.
KS 60 E GB 240V	005.25.212

 System accessories and circular saw blades are available to order separately, see **Sections 1 and 2** of this Directory

PAGE AMENDED
18.04.24/1