

Festool KP 65/2 trimming machine



- > Ergonomic handle location for easy, effortless trimming, even on thick edging
- > Patented eccentric fine adjustment for precision impact trimming
- > Tabletop on both sides of the trimming machine allows the user to trim left and right panel edges from above - with a perfect view of the workpiece
- > For trimming plastic edging with a height of 18 - 65 mm and a thickness of 0.5 - 2.0 mm (depending on material)
- > For PVC, acrylic and thin wooden veneer edging (depending on material)
- > Impact trimming function (for round table) and trimming of panel edges (final trimming) with a single machine
- > **Technical data:**
 - Trimming height: 65 mm
 - Trimming thickness: 2 mm
- > Order qty: 1 pc

	Cat. No.
Trimming machine	002.22.014

Festool AP-KA65 adapter plate



- > For mounting the edge bander on a workbench
- > For small batches, straight edges, free form elements and gluing inclined edges, angle from 0-47°
- > Allows the user to swivel the machine (0-47°) in the bench and position the workpiece horizontally during edging - for convenient and safe guidance, even with larger objects
- > Sliding guides for guiding the workpiece safely
- > For using the edge bander KA 65 as a bench-mounted machine
- > Adapter plate for installation in the MFT (with perforated board KA 65, order no. 500366) or a separate workbench
- > **Technical data:**
 - Dimensions length x width: 254 x 420 mm
 - Min. installation height: 150 mm
 - Cutting angle adjustment: 0-47 °
- > **Supplied with:**
 - Mounting plate for edge bander complete with 15 sliding guides
 - Additional roll
- > Order qty: 1 pc

	Cat. No.
Adapter plate	002.22.012

Festool LP-KA65 MFT/3 perforated top



- > With cut-outs for stationary use of the edge bander in the MFT multifunction table in combination with the adapter plate AP-KA 65
- > For small batches, straight edges, free form elements and gluing inclined edges, angle from 0-47°
- > Guide plates for guiding the workpiece safely, easy to attach via integral M4 reducing rings
- > Allows the user to swivel the machine (0-47°) in the bench in combination with adapter plate AP-KA 65 and position the workpiece horizontally during edging - for convenient and safe guidance, even with larger objects
- > **Technical data:**
 - Dimensions length x width: 1102 x 718 mm
- > Order qty: 1 pc

	Cat. No.
Perforated top	002.22.011