

FESTOOL ETS EC 150 ECCENTRIC SANDER

The ETS EC 150 can be positioned in all ways; overhead, on vertical areas or narrow edges. With a high-performance, brushless EC-TEC motor, the compact ETS EC 150 is ideal for one-handed, effortless work with perfect handling and sanding results.

- > The perfect finishing sander in the compact class
- > Stepless speed preselection, constant speed even under load
- > Very high surface quality thanks to 3 or 5 mm sanding stroke
- > Longlife thanks to EC technology and sanding pad brake with carbide tip
- > Compact design and weighing only 1.2 kg for optimal ergonomic work conditions



Festool ETS EC 150 Eccentric sander, 240V



- > Antistatic function - prevents static charge from accumulating
- > EC-TEC - drive generates an extraordinary amount of power while consuming extremely low amounts of energy
- > MMC electronics - Multi Material Control power electronics with constant adjustable speed and temperature monitor for work on all types of material
- > MULTI-JETSTREAM 2 principle - Sanding system with integral dust conveying concept. With the patented MULTI-JETSTREAM 2 principle
- > Vibration stop - Patented VS balancing so that tools run smoothly during sanding, which makes working less hazardous
- > Plug it - Removable, replaceable mains cable with safety lock for quick conversion
- > StickFix - Quick, economical fastening system for abrasives - no adhesives, no clamping
- > **Technical data:**
 - Power consumption: 400 W
 - Eccentric motion speed: 6000-10000 RPM
 - Sanding stroke: 3 / 5 mm dependant on version
 - Interchangeable sanding pad: Ø 150 mm
 - Dust extraction connection: Ø 27 mm
 - Weight: 1.2 kg
- > **Supplied with:**
 - MULTI-JETSTREAM 2 M8 sanding pad Ø 150 mm (extra soft SW or soft W dependant on version)
 - Operation tool
 - In a Systainer SYS3 M 187
- > Order qty: 1 set



System accessories and abrasives are available to order separately, see **Sections 1** and **2** of this Directory

Version / Model No.	Cat. No.
ETS EC 150/3 EQ-Plus GB (sanding stroke 3) Extra soft SW sanding pad Ø 150 mm	005.25.257
ETS EC 150/5 EQ-Plus GB 240V (sanding stroke 5) Soft W sanding pad Ø 150 mm	005.25.258