

FESTOOL ETSC 2 125 CORDLESS ECCENTRIC SANDER

The ETSC 2 cordless eccentric sander offers maximum freedom of movement when sanding. The integrated LED light ring improves your view of the surface and reveals any unevenness during sanding. The eccentric sanding motion creates outstanding surface quality – with no need for costly rework.

- > The integrated LED light ring improves your view of the surface and makes it easier to see any unevenness. The integrated light and eccentric sanding motion of the ETSC 2 ensure a virtually flawless surface
- > Its low height means that the sander lies directly in your hand – for convenient sanding, whether you are working on the plane or overhead
- > The cordless eccentric sander offers maximum freedom of movement when sanding, without irritating cables getting in the way. The powerful 4.0 Ah battery enables fast work progress and is compatible with your 18V cordless machines and battery chargers



Festool ETSC 2 125 cordless eccentric sander



ETSC 2 125-Basic



ETSC 2 125 4.0 I-Plus

- > Antistatic function - prevents static charge from accumulating
- > EC-TEC - The EC-TEC drive concept generates an extraordinary amount of power while consuming extremely low amounts of energy
- > Lithium-ion (Li) - Fitted with high-performance lithium-ion battery pack
- > Cleantec dust extraction - standard connector
- > MMC digital electronics - Processor controlled 'Multi Material Control' power electronics provide adjustable and constant speeds as well as temperature monitoring for work on all types of material
- > Multi-Jetstream 2 principle - Sanding with integrated dust conveying system
- > Vibration stop - Patented VS balancing so that tools run smoothly during sanding, which makes working less hazardous
- > Turbo dust extraction - Turbo dust extraction ensures clean, dust-free air and a clear view of the workpiece
- > StickFix - quick, economical fastening system for abrasives - no adhesives, no clamping
- > Bluetooth® communication between battery pack and extractor
- > **Technical data:**
 - Battery voltage: 18 V
 - Idle engine speed: 6000-10000 RPM
 - Li-ion battery capacity: 4.0 Ah
 - Sanding stroke: 3.5 mm
 - Interchangeable sanding pad: Ø 125 mm
 - Dust extraction connection: Ø 27 mm
 - Weight with Li-ion: 1.2 kg
- > **Supplied with:**
 - StickFix sanding pad, Ø 125 mm (soft-HT)
 - PR ETSC 2 125 Protector
 - SB-Long-life ETSC 2 dust collection bag
 - In a Systainer SYS3 M 187
- > Order qty: 1 set



I-Plus version: The 18 V battery pack can be replaced with the plug it-mains adapter and cable to create a mains-powered machine with an unlimited running time for continuous electrical operation



System accessories, abrasives, battery and charger are available to order separately, see **Sections 1** and **2** of this Directory

Version / Model No.	Cat. No.
ETSC 2 125-Basic Without battery pack, without charger, in SYSTAINER SYS3 M 187	000.00.717
ETSC 2 125 4.0 I-Plus 2x BP 18 Li 4.0 HPC-ASI battery pack, rapid charger TCL 6, in SYSTAINER SYS3 M 187	000.00.718