

FESTOOL ROTEX RP 90 DX GEARED ECCENTRIC SANDER

Round tool that also sands in corners. Four devices in one: Smaller pad. Greater versatility. The new ROTEX RO 90 geared eccentric sander with the tried-and-tested ROTEX principle makes quick work of coarse sanding, fine sanding and polishing tasks. Now suitable for working in corners.

- > Four tools in one: for coarse sanding, fine sanding, delta sanding and polishing. Resulting in low investment costs and savings on working time
- > Durable eccentric bearings, a double-sealed gear unit and a dustproof switch extend the service life of the machine
- > ROTEX rotary motion for convenient polishing – the reduced speed keeps the temperature low and prevents the polish from clouding or spraying off
- > FastFix sanding pad system, tool-less
- > Eccentric motion for high-quality, scratch-free surfaces



Power Tools

1

Festool ROTEX RP 90 DX geared eccentric sander



- > Ideal for coarse sanding, fine sanding, delta sanding and polishing
- > ROTEX rotary motion for efficient material removal
- > Eccentric motion for high-quality, scratch-free surfaces
- > FastFix sanding pad system, tool-less
- > Ideal ergonomic grip positions
- > Sanding up to the edge thanks to the Festool PROTECTOR
- > Effortless work thanks to a weight <1.5 kg
- > **Technical data:**
 - Power consumption: 400 W
 - ROTEX rotary motion speed: 260-520 RPM
 - Eccentric motion speed: 3500-7000 RPM
 - Sanding stroke: 3 mm
 - FastFix sanding pad: Ø 90 mm
 - Dust extraction connection: Ø 27 mm
 - Cable length: 4.0 m
 - Weight: 1.4 kg
- > **Supplied with:**
 - FastFix sanding pad, Ø 90 mm (soft-HT)
 - StickFix sanding pad V93
 - Festool PROTECTOR
 - In a Systainer SYS3 M 187
- > Order qty: 1 set

Please note: Plug-it cable is supplied with a UK plug

 System accessories and abrasives are available to order separately, see **Sections 1 and 2** of this Directory

Version / Model No.	Cat. No.
ROTEX RO 90 DX FEQ-Plus 240V in SYSTAINER SYS3 M 187	005.25.288
ROTEX RO 90 DX FEQ-Plus 110V in SYSTAINER SYS3 M 187	005.25.289