

FESTOOL CLEANTEC CTL MIDI I DUST EXTRACTOR

Thanks to the low weight and compact, ergonomic design, the CTL MIDI is perfect for transportation. Whether you need it for cleaning during assembly, installation or renovation work, the wet/dry extractor is perfect for extracting small to medium volumes of dust and dirt. For class L dust.

- > Ideal for use on the go thanks to compact dimensions, low weight and robust chassis
- > Touch operation for intuitive control of the mobile dust extractor
- > Keep working until the filter bag is full thanks to manual dedusting
- > Internal hose holder for safe and clean transport of the smooth suction hose



Festool CLEANTEC CTL Midi I mobile dust extractor



- > Antistatic function - prevents static charge from accumulating
- > Smooth suction hose - with a smooth exterior which allows it to slide over surfaces perfectly
- > Electronic - Speed control for adjusting to all types of materials.
- > CLEANTEC connecting system - Integrated bayonet fitting as the connecting element between the extractor and the tool
- > Bluetooth® Autostart - communication between battery and extractor
- > **Technical data:**
 - Voltage: 110/240 V
 - Power consumption: 350-1200 W
 - Max. volume flow: 3.700 litres/min
 - Max. vacuum: 24000 Pa
 - Filter surface area: 3.369 cm²
 - Rubber insulation mains cable: 7.5 m
 - Container/filter bag capacity: 15/12.5 litres
 - Dimensions L x W x H: 470 x 320 x 495 mm
 - Max. appliance socket connected load: 2200 W
 - Weight: 11.3 kg
- > **Supplied with:**
 - Smooth suction hose Ø 27/32 x 3.5 m AS/CT
 - Bluetooth® functionality for extractor, remote switch-on for cordless tools
 - SELCLEAN filter bag SC-FIS-CT MINI/MIDI
 - Hose holder
 - Cable holder
 - SYS-Dock with T-LOC function
 - In a carton
- > Order qty: 1 set



System accessories are available to order separately, see pages **1.102-115**

Version / Model No.	Cat. No.
CTL MIDI I GB 110V	005.24.914
CTL MIDI I GB 240V	005.24.915