

FESTOOL CLEANTEC CTM 26 EI DUST EXTRACTOR

The CLEANTEC CTM 26 EI offers a large 26 litre container volume combined with compact dimensions. It comes with touch operation for intuitively controlling your extractor. It has a permanently installed Bluetooth® interface for starting the extractor using a Festool cordless tool or automatically starting it with optional remote control. Or you can connect it to the Festool app.

- > The smooth, anti-static suction hose can be handily stowed away in the integrated hose holder. T-LOC enables you to quickly connect Systainers, pre-separators or Workcenters. This means that your extractor becomes the central point of the system
- > Touch operation for simple control of the extractor
- > Automatic electrical outlet module - For corded power tools. Starts up the power tool and automatically starts up your extractor too
- > Suction power - Depending on the application, this can be set to five levels
- > T-LOC function makes it easy to install Systainers on the mobile dust extractor
- > Constantly high suction because of the compact high performance turbine
- > Can be retrofitted: With compressed-air module or electrical outlet module



Festool CLEANTEC CTM 26 EI mobile dust extractor



- > For hazardous wood dust and mineral dust from dust class M with limit values > 0.1 mg/m³
- > Suitable for both wet and dry extraction
- > Antistatic function - prevents static developing during work
- > Smooth suction hose with conical geometry for high suction power and seamless processes without catching
- > FlowDetect - The flow sensor checks for a minimum air speed of 20 m/sec and issues a warning if the air speed falls below this value
- > Electronic - Speed control for adjusting to all types of materials
- > CLEANTEC connecting system - Integrated bayonet fitting as the connecting element between the extractor and the tool
- > Bluetooth® Autostart - The integrated Bluetooth® technology starts the dust extractor automatically via Bluetooth® battery packs or optional remote control
- > Dust class M
- > **Technical data:**
 - Voltage: 230 V
 - Power consumption: 350-1200 W
 - Max. volume flow: 3900 litres/min
 - Max. vacuum: 24000 Pa
 - Filter surface area: 6318 cm²
 - Rubber insulation mains cable: 7.5 m
 - Container/filter bag capacity: 26/24 litres
 - Dimensions L x W x H: 630 x 365 x 540 mm
 - Max. appliance socket connected load: 1610 W
 - Weight: 13.9/17.0 kg
- > **Supplied with:**
 - Main filter
 - SELF-CLEAN filter bag
 - Smooth suction hose Ø 27/32 x 3.5 m AS/CTR
 - End cap for intake adapter
 - In a carton
- > Order qty: 1 pc



System accessories are available to order separately, see pages **1.102-115**

Version / Model No.

Cat. No.

CTM 26 EI 230V

000.00.701

PAGE CREATED
29.04.25