

FESTOOL CLEANTEC CT 26 AC DUST EXTRACTOR

Prevent clogged filters with the CLEANTEC AC. It has an automated filter cleaning system, AUTOCLEAN, which keeps the filter clean and maintains a constant suction power. Can be individually retrofitted with an additional Bluetooth® module for remote control on the suction hose or automatic start via the Bluetooth® battery pack.

- > AUTOCLEAN automatic main filter cleaning system with infinitely adjustable cleaning intervals for consistently high suction power
- > Can be individually retrofitted with an additional socket, compressed air or Bluetooth® module for remote control on the suction hose or automatic start via the Bluetooth® battery pack
- > Maximum utilisation of the container volume – the gross volume is the same as the net volume
- > Smooth suction hose and optimised SYS-Dock with cord holder and T-LOC function for conveniently connecting SYSTAINERS to the mobile dust extractor



Festool CLEANTEC CTM Midi I mobile dust extractor



CTL 26 E AC



CTM 26 E AC

- > Antistatic function - prevents static charge from accumulating
- > Smooth suction hose - with a smooth exterior which allows it to slide over surfaces perfectly
- > Electronic - Speed control for adjusting to all types of materials
- > CLEANTEC connecting system - Integrated bayonet fitting as the connecting element between the extractor and the tool
- > AUTOCLEAN automatic main filter cleaning system with infinitely adjustable cleaning intervals
- > Bluetooth® Autostart - communication between battery and extractor
- > **Technical data:**
 - Voltage: 240 V
 - Power consumption: 350-1200 W
 - Max. volume flow: 3.900 litres/min
 - Max. vacuum: 24000 Pa
 - Filter surface area: 6.318 cm²
 - Rubber insulation mains cable: 7.5 m
 - Container/filter bag capacity: 26/24 litres
 - Dimensions L x W x H: 630 x 365 x 540 mm
 - Max. appliance socket connected load: 2400 W
 - Weight: 14.7 kg
- > **Supplied with:**
 - High-performance main filter
 - SELCLEAN filter bag disposal bag
 - Smooth suction hose Ø 27/32 x 3.5 m AS/CT
 - Hose holder
 - Cable holder
 - SYS-Dock with T-LOC function
 - In a carton
- > Order qty: 1 set



System accessories are available to order separately, see pages **1.102-115**



Most of the products you will find in this catalogue are available within 24 hours. However, to be able to offer the breadth of range in our collection, a small number of products have a longer lead time. Please call 0800 171 2909 for an accurate delivery date when you see this symbol.

Version / Model No.	Cat. No.
CTL 26 E AC GB 240V	005.25.242
CTM 26 E AC GB 110V, end cap for intake adapter	005.25.386 
CTM 26 E AC GB 240V, end cap for intake adapter	005.25.243 