

FESTOOL CLEANTEC CTM 26 EI AC DUST EXTRACTOR

Compared with its predecessor, the CLEANTEC CTM 26 EI AC boasts more effective AUTOCLEAN main filter cleaning, ensuring a consistently high suction power, longer working intervals and a longer filter service life with lower maintenance effort.

- > It has a permanently installed Bluetooth® interface for starting the extractor using a Festool cordless tool or automatically starting it with optional remote control. Your extractor is also connected to the Festool app
- > The smooth, anti-static suction hose can be handily stowed away in the integrated hose holder
- > Touch operation for simple control of the extractor
- > Automatic electrical outlet module - For corded power tools. Starts up the power tool and automatically starts up your extractor too
- > Suction power - Depending on the application, this can be set to five levels
- > T-LOC function makes it easy to install Systainers on the mobile dust extractor
- > Constantly high suction because of the compact high performance turbine
- > Can be retrofitted: With compressed-air module or electrical outlet module



Festool CLEANTEC CTM 26 EI AC mobile dust extractor



- > For hazardous wood dust and mineral dust from dust class M with limit values > 0.1 mg/m³
- > Suitable for both wet and dry extraction
- > Antistatic function - prevents static developing during work
- > Smooth suction hose with conical geometry for high suction power and seamless processes without catching
- > FlowDetect - The flow sensor checks for a minimum air speed of 20 m/sec and issues a warning if the air speed falls below this value
- > Electronic - Speed control for adjusting to all types of materials
- > CLEANTEC connecting system - Integrated bayonet fitting as the connecting element between the extractor and the tool
- > AUTOCLEAN automatic main filter cleaning system with infinitely adjustable cleaning intervals
- > Bluetooth® Autostart - The integrated Bluetooth® technology starts the dust extractor automatically via Bluetooth® battery packs or optional remote control
- > Dust class M
- > **Technical data:**
 - Voltage: 110/230 V
 - Power consumption: 350-1200 W
 - Max. volume flow: 3900 litres/min
 - Max. vacuum: 24000 Pa
 - Filter surface area: 6318 cm²
 - Rubber insulation mains cable: 7.5 m
 - Container/filter bag capacity: 26/24 litres
 - Dimensions L x W x H: 630 x 365 x 540 mm
 - Max. appliance socket connected load: 1610 W
 - Weight: 14.7/17 kg
- > **Supplied with:**
 - High-performance main filter
 - SELCLEAN filter bag
 - Disposal bag
 - Smooth suction hose Ø 27/32 x 3.5 m AS/CTR
 - End cap for intake adapter
 - In a carton
- > Order qty: 1 pc



System accessories are available to order separately, see pages **1.102-115**

Version / Model No.	Cat. No.
CTM 26 EI AC 110V	000.00.709
CTM 26 EI AC 230V	000.00.703