

FESTOOL CLEANTEC CTM MINI DUST EXTRACTOR

The CLEANTEC CTM MINI offers a 7.5 litre container volume combined with compact dimensions. It comes with touch operation for intuitively controlling your extractor. It has a permanently installed Bluetooth® interface for starting the extractor using a Festool cordless tool or automatically starting it with optional remote control. Or you can connect it to the Festool app.

- > The smooth, anti-static suction hose can be handily stowed away in the integrated hose holder. T-LOC enables you to quickly connect Systainers, pre-separators or Workcenters. This means that your extractor becomes the central point of the system
- > Touch operation for simple control of the extractor
- > Automatic electrical outlet module - For corded power tools. Starts up the power tool and automatically starts up your extractor too
- > Suction power - Depending on the application, this can be set to five levels
- > T-LOC function makes it easy to install Systainers on the mobile dust extractor
- > Constantly high suction because of the compact high performance turbine
- > Can be retrofitted: With compressed-air module or electrical outlet module



Festool CLEANTEC CT MINI mobile dust extractor



- > For dust with limit values > 1 mg/m³
- > Suitable for extraction of mineral dust during more minor sanding, milling, sawing or drilling work (e.g. dry, mortarless construction)
- > Suitable for both wet and dry extraction (special wet filter required for wet extraction)
- > Ideal for mobile use in service and installation work and for final cleaning
- > Electronic - Speed control for adjusting to all types of materials
- > CLEANTEC connecting system - Integrated bayonet fitting as the connecting element between the extractor and the tool
- > Bluetooth® Autostart - The integrated Bluetooth® technology starts the dust extractor automatically via Bluetooth® battery packs or optional remote control
- > Dust class L
- > **Technical data:**
 - Voltage: 110/230 V
 - Power consumption: 350-1200 W
 - Max. volume flow: 3700 litres/min
 - Max. vacuum: 24000 Pa
 - Filter surface area: 3508 cm²
 - Rubber insulation mains cable: 7.5 m
 - Container/filter bag capacity: 10/7.5 litres
 - Dimensions L x W x H: 472 x 322 x 455 mm
 - Max. appliance socket connected load: 180 W
 - Weight: 11.2 kg
- > **Supplied with:**
 - Main filter
 - SELF-CLEAN filter bag
 - Smooth suction hose Ø 27/32 x 3.5 m AS/CTR
 - In a carton
- > Order qty: 1 pc

Version / Model No.	Cat. No.
CT MINI I 110 V	000.00.892
CT MINI I 230 V	008.53.408
CT 15 230V	005.25.448