



Trend trimming cutter, 1/4" shank



- > Shank Ø: 1/4"
- > For trimming and bevelling timber, lippings and plastic laminate edges or any shaping applications
- > Self-guiding trimmer with bearings mounted on end of cutter
- > Tip material: Tungsten carbide
- > Order qty: 1 pc

Diameter	Usable length	Cat. No.
Ø 12.7 mm	16 mm	000.00.456


Trend Professional bearing guided 90° trimming cutter, 1/4" shank



- > Shank Ø: 1/4"
- > For laminate and template work
- > For bringing decorative laminates and veneers flush to an edge or for templating work
- > Ideal for worktop fitting for flush trimming edging laminates for a professional finish
- > Bearing guide can be used with templates on thin stock, ideal for pattern making or replicating components. Narrow diameter ideal for following tighter curves on more intricate work
- > 1/4" shank for easy control in smaller routers with 'K' mark shank to ensure safe working practices
- > Tip material: Tungsten carbide
- > Order qty: 1 pc

Diameter	Usable length	Cat. No.
Ø 9.5 mm	12.7 mm	000.00.491


Trend guided 90° trimmer, 1/4" shank



- > Shank Ø: 1/4"
- > Two flute mini-trim with guide bearing will profile intricate shapes
- > Max. 2.0 mm trimming
- > Ideal for acrylic trimming
- > Tip material: Tungsten carbide
- > Order qty: 1 pc

Diameter	Usable length	Cat. No.
Ø 6.3 mm	25.4 mm	000.00.473

Trend guided 90° trimmer, 1/2" shank



- > Shank Ø: 1/2"
- > Self-guiding trimmer with bearings mounted on end of cutter
- > For trimming plastic or plywood overlay. For copy profiling, use the bearing to follow a template or base edge of board
- > An approximate 3 mm overlap should be left before copy profiling
- > When using plastic laminate adhesive to dry before trimming
- > This avoids clogging the guide bearing
- > Tip material: Tungsten carbide
- > Order qty: 1 pc

Diameter	Usable length	Cat. No.
Ø 12.7 mm	38.1 mm	000.00.480