

Trend Professional lock jig



- > A site-tough routing jig with interchangeable templates to cut lock and face-plate recesses in timber doors
- > Steel construction and tool-free setup deliver speed and accuracy
- > Ideal for all popular mortice sash locks, dead locks and tubular latches from leading ironmongery brands
- > Full-length adjustable fence to accommodate all doors between 34 mm and 58 mm thick
- > Quick-release clamps with non-marring pads ensure the jig is held securely
- > 20 interchangeable templates to suit all common lock case and face plate sizes
- > Easy reference chart ensures that correct templates are found quickly
- > The jig requires: 1/2"/12 mm plunge router (80 mm plunge depth), 1/2"/12 mm router cutter (12 mm cut diameter x 63 mm cut length), and 30 mm guide bush
- > Steel construction for maximum strength, durability and accuracy
- > Order qty: 1 pc

Cat. No.	
Professional lock jig	000.00.563

Trend Two part hinge jig



- > The two part contractor hinge jig is a portable fully adjustable block template set designed for recessing hinges in wooden doors and frames using a plunge router
- > Adjustable quick-release aperture blocks are used to set the hinge position and length, and feature Trend's tool-free, patented thumb-turn locking mechanism for fast, accurate adjustments
- > Adjustable edge guides are used to set the hinge leaf width and can be positioned using indexed locations (20, 25, and 30 mm) or anywhere within the open channel, for non-standard widths up to 35 mm
- > Lightweight anodised aluminium rails for optimum strength, durability, accuracy and a smooth router running surface
- > Fire door compatibility allows the 2nd hinge to be positioned 20" from the top of the door
- > Bradawl attachment allows the jig to be quickly secured to doors and frames (included)
- > Aluminium end plate allows the jig to fit both door and frame with minimal adjustment
- > 25 mm rail depth allows jig to be used against fixed door stops up to 25 mm thick
- > Two part body for compact transportation
- > Requires: Plunge router (1/4"/8 mm collet), cutter (1/4"/8 mm shank x 12 mm cut diameter x 70 mm overall length) and corner chisel
- > Consists of:
 - Two part skeleton hinge jig
 - Guide bush (16 mm diameter)
 - Bradawl attachment
 - Robust carry bag
- > Order qty: 1 pc

Cat. No.	
Two part hinge jig	000.00.564