


- > The fischer frame fixing DuoXpand with two anchoring depths is approved with the fischer countersunk or hexagonal screw for multiple fixings of non-load-bearing systems in concrete, masonry and aerated concrete.
- > Thanks to its special geometry and the material combination, the anchor expands optimally in the respective building material.
- > The range includes diameters 8 and 10 and anchor lengths up to 120 mm.
- > The DuoXpand with the countersunk screw is particularly suitable for fixing timber to concrete or masonry.
- > The DuoXpand with the hexagon head screw and moulded-on washer is particularly suitable for fixing metal to concrete or masonry.

Fischer frame fixing DuoXpand with countersunk head screw



- > Clever combination of design and material for a secure installation in the building material
- > Expansion element with two anchoring depths for flexible use
- > Approved multiple fastening of non-load-bearing systems in concrete and masonry
- > Side ribs prevent rotation in the drill hole for convenient installation
- > Pre-assembled safety screw with countersunk head




Anchor length	Drill Ø	Min. drill hole depth	Cat. No.	Order Qty
120 mm	8 mm	130 mm	051.69.007	50
80 mm	10 mm	90 mm	051.69.008	50

Fischer frame fixing DuoXpand with hexagon head screw



- > Clever combination of design and material for a secure installation in the building material
- > Expansion element with two anchoring depths for flexible use
- > Approved multiple fastening of non-load-bearing systems in concrete and masonry
- > Side ribs prevent rotation in the drill hole for convenient installation.
- > Pre-assembled safety screw with hexagonal head and preformed washer



Anchor length	Drill Ø	Min. drill hole depth	Cat. No.	Order Qty
80 mm	8 mm	90 mm	051.69.009	50
100 mm	10 mm	110 mm	051.69.010	50

TOOLS & CONSUMABLES 2023. © Häfele U.K. Ltd 2023. Dimensional data not binding. We reserve the right to alter specifications without notice.