


- > The DuoHM cavity plug covers all common building material thicknesses from 9.5 - 30 mm with just one length.
- > Thanks to the unique combination of nylon and metal, the DuoHM enables high loads and maximum flexibility in panel building materials.
- > The metal sleeve folds behind the building material and presses against the back of the panel, while the plastic part knots in the panel.
- > The DuoHM is installed quickly and easily using a cordless screwdriver without any additional setting tools. This reduces the installation time by up to 50% compared to conventional panel plugs.
- > Thanks to the metric internal thread, the attachment can be screwed in and unscrewed several times.
- > In addition to the screw supplied, the DuoHM can also be used with other metric screws.
- > The nylon anti-rotation lock protects the surface of the building material from damage. Due to the narrow plug edge, the anchor is no longer visible behind the attachment.

Fischer cavity fixing DuoHM



- > Up to 50% faster installation than comparable panel plugs
- > Easy installation with cordless screwdriver without setting tool
- > One plug length per diameter for all common building material thicknesses
- > High loads thanks to 2-component technology
- > Nylon plug edge prevents damage to the building material surface



Anchor length	Drill Ø	Min. drill hole depth	Panel thickness	Cat. No.	Order Qty
55 mm	10 mm	55 mm	9.5 - 30 mm	051.69.004	55
55 mm	12 mm	55 mm	9.5 - 30 mm	051.69.005	55

TOOLS & CONSUMABLES 2023. © Häfele U.K. Ltd 2023. Dimensional data not binding. We reserve the right to alter specifications without notice.