


SPECIAL SCREWS



Please order screws in multiples of order quantity shown

Hospa screw, flat head




- > Galvanized steel
- > Fully threaded
- > With PZ cross slot head



Ø x Length	Head Ø	Driver required	Cat. No.	Order Qty
3.0 x 20 mm	7.8 mm	PZ1	016.10.555	1000
3.0 x 25 mm	7.8 mm	PZ1	016.10.573	1000
3.5 x 25 mm	8.5 mm	PZ2	016.10.671	1000
3.5 x 30 mm	8.5 mm	PZ2	016.10.680	1000
3.5 x 35 mm	8.5 mm	PZ2	016.10.699	1000
4.0 x 20 mm	9.5 mm	PZ3	016.10.840	1000
4.0 x 25 mm	9.5 mm	PZ3	016.10.859	1000
4.0 x 30 mm	9.5 mm	PZ3	016.10.868	1000
4.0 x 35 mm	9.5 mm	PZ3	016.10.877	500
4.0 x 40 mm	9.5 mm	PZ3	016.10.886	500


Pocket hole screw, domed head



- > Self tapping anti-split
- > Partially threaded
- > Domed head with square drive bit
- > Galvanized steel

Ø x Length	Cat. No.	Order Qty
3.75 x 30 mm	010.99.301	1 pack (500 pcs)

Wood screw, countersunk head




- > DIN 97 with single slot
- > Partially threaded
- > Nickel-plated steel or bright brass



Ø x Length	Nickel-plated steel	Bright brass	Order Qty
2.5 x 16 mm	011.04.230	-	100
2.5 x 20 mm	011.04.249	-	100
2.5 x 12 mm	-	011.00.214	100
2.5 x 16 mm	-	011.00.232	100
2.5 x 20 mm	-	011.00.241	100


Dry wall screw



- > Bugle head
- > Sharp point
- > Black phosphate steel


Ø x Length	Driver required	Cat. No.	Order Qty
3.5 x 25 mm	PH2	015.99.801	1000
3.5 x 32 mm	PH2	015.99.802	1000
3.5 x 38 mm	PH2	015.99.804	1000
3.5 x 42 mm	PH2	015.99.805	1000
3.5 x 45 mm	PH2	015.99.806	1000
3.5 x 50 mm	PH2	015.99.807	1000
4.2 x 65 mm	PH2	015.99.813	500
4.2 x 75 mm	PH2	015.99.814	500

Collated dry wall screws



Ø x Length	Driver required	Cat. No.	Order Qty
3.5 x 35 mm	PH2	015.99.853	1000
3.5 x 38 mm	PH2	015.99.854	1000


Carcase assembly screw, funnel head



- > Black steel
- > Fully threaded
- > Funnel head with PZ cross slot, hi-lo thread

Ø x Length	Driver required	Cat. No.	Order Qty
4.0 x 33 mm	PZ2	015.45.301	1000
4.0 x 45 mm	PZ2	015.45.302	1000

Panel mounting screw



- > For Ø 5 mm drilled hole
- > Flat head with PZ cross slot
- > Galvanized steel

Length	Driver required	Cat. No.	Order Qty
13.5 mm	PZ2	013.10.149	200
27.5 mm	PZ2	013.10.283	100