

# SECURITY SCREWS AND TOOLS

The need to safeguard against theft and vandalism is an increasingly essential part of many design specifications. To counter these threats, this tamper-resistant range can be used in many varied applications.

## 6-Lobe / Machine screw, countersunk head



Requires special bit for installation and removal, order separately: e.g. Cat. No. 006.37.022 for driver T20

- > Star drive with internal pin in the aperture
- > 304 stainless steel

| Size       | Driver size | Cat. No.   | Order Qty |
|------------|-------------|------------|-----------|
| M4 x 10 mm | T20         | 020.04.064 | 200       |
| M4 x 12 mm | T20         | 020.04.065 | 200       |
| M4 x 16 mm | T20         | 020.04.066 | 200       |
| M4 x 20 mm | T20         | 020.04.067 | 200       |
| M4 x 25 mm | T20         | 020.04.068 | 200       |
| M4 x 30 mm | T20         | 020.04.069 | 200       |
| M5 x 16 mm | T25         | 020.04.096 | 200       |
| M5 x 20 mm | T25         | 020.04.097 | 200       |
| M5 x 25 mm | T25         | 020.04.098 | 200       |
| M5 x 30 mm | T25         | 020.04.099 | 200       |
| M6 x 16 mm | T30         | 020.04.126 | 200       |
| M6 x 20 mm | T30         | 020.04.127 | 200       |
| M6 x 25 mm | T30         | 020.04.128 | 200       |
| M6 x 30 mm | T30         | 020.04.129 | 200       |
| M6 x 40 mm | T30         | 020.04.131 | 200       |
| M6 x 50 mm | T30         | 020.04.133 | 200       |

## 6-Lobe / Resistorex security screw, button head



Requires special bit for installation and removal, order separately: Cat. No. 006.37.024

- > Star drive with internal pin in the aperture
- > 304 stainless steel

| Size        | Driver size | Cat. No.   | Order Qty |
|-------------|-------------|------------|-----------|
| 6.3 x 38 mm | T27         | 010.93.081 | 100       |

## 6-Lobe / Resistorex security screw, countersunk



Requires special bit for installation and removal, order separately: e.g. Cat. No. 006.37.020 for driver T10

- > Star drive with internal pin in the aperture
- > 304 stainless steel

| Size        | Driver size | Cat. No.   | Order Qty |
|-------------|-------------|------------|-----------|
| 2.9 x 13 mm | T10         | 010.93.048 | 100       |
| 2.9 x 19 mm | T10         | 010.93.049 | 100       |
| 3.5 x 16 mm | T15         | 010.93.051 | 100       |
| 3.5 x 19 mm | T15         | 010.93.041 | 100       |
| 3.5 x 25 mm | T15         | 010.93.042 | 100       |
| 4.2 x 32 mm | T20         | 010.93.043 | 100       |
| 4.2 x 38 mm | T20         | 010.93.044 | 100       |
| 4.2 x 50 mm | T20         | 010.93.045 | 100       |
| 4.8 x 38 mm | T25         | 010.93.046 | 100       |
| 4.8 x 50 mm | T25         | 010.93.047 | 100       |

## 6 Lobe pin 1/4" special insert bit



- > To suit 6-lobe / Machine and Resistorex security screws
- > Order qty: 1 pc

| Size | Cat. No.   |
|------|------------|
| T10  | 006.37.020 |
| T15  | 006.37.021 |
| T20  | 006.37.022 |
| T25  | 006.37.023 |
| T27  | 006.37.024 |
| T30  | 006.37.025 |



Please order security screws in multiples of order quantity shown