



BUTTON-FIX™ PANEL CONNECTING FITTINGS

System includes four types of connecting fittings for use with special buttons to connect panels in parallel or at 90°.

Button-fix™ type 1 Fix, for parallel panels




- > Connects parallel panels and is ideal for applications where strength and security is paramount
- > Engage the buttons in the connector and slide the panel down by 15 mm until Button-fix™ goes 'click', can also be configured sideways
- > When surface mounted an 8 mm gap is created between the two attaching panels
- > Alternatively, you can rebate connector to reduce the gap between the two attaching panels to only 3 mm
- > Glass filled nylon
- > Order qty: Multiples of 100 pcs





Ø 5 mm pan head screws
for surface-mounted option

15 mm fall to
engage panel




Ø 4.5 mm csk screws
for rebated option

... or 15 mm slide to
engage panel




Cat. No.
Type 1 262.94.000


Button-fix™ type 1 flush Fix, for flush fitting of parallel panels



- > For applications where panel to panel contact is required and fits a simple oval rebate
- > Can be rebated into the edge of a panel of at least 28 mm thick, in particular hollow core panels or the face of a panel of at least 18 mm thick
- > Allows you to fit panels together with no gap between, when fixing panels at least 18 mm thick (we recommend Euro screws for fixing into panels 18 - 22 mm)
- > Suitable for secret fixing of drawer fronts or connecting work surfaces to carcasses, exhibition stands and peg rails
- > Glass filled nylon
- > Order qty: Multiples of 100 pcs



22 x 56 x 8 mm oval rebate
Ø 4.5 mm countersunk screws



15 mm fall to
engage panel



Cat. No.
Type 1 flush 262.94.014

YOU ALSO NEED:



BUTTON-FIX™ BUTTON
Page 7.69



FIXING SCREWS
Pages 13.6-20

OPTIONAL ACCESSORIES
Pages 7.70-71