

FREE FOLD BI-FOLD LIFT UP FITTING

Complete fitting sets, or components available separately.




- > Complete fitting set
- > Time saving installation provided by plugs, pre-mounted euro screws and clip fixing for front panel
- > For use in furniture in kitchens, living rooms, bathrooms and offices
- > For two-piece wooden flaps, flap locks in any position (multi-position stop function)
- > Assisted opening and soft closing
- > For flap heights 720 (700-780) mm or 550 (540-580) mm
- > Adjustable fitting, suitable for flap weights 2-20.3 kg
- > Finger safe
- > Min. 110° opening concealed hinges are required - order Quick Fixing 110° hinge and mounting plate separately




Order Quick Fixing 110° hinge and mounting plate separately shown on page **9.30**

Finger protection



To avoid injuries the hinge comes apart when fingers get trapped unintentionally in the gap of the flap


Adjustment facility




Height adjustment
±3 mm




Holding power adjustment



Centre pull adjustment



Side adjustment
± 3 mm



Opening angle adjustment

Free Fold lift up flap fitting set

- > Set consists of:
 - 1x Pair Free Fold piston arms, nickel-plated steel with grey or white coloured plastic cover caps
 - 2x Brackets, for mounting piston arms, from frame width 45 mm, screw fixing, grey plastic
 - 2/3x Finger safe connecting hinges, for frame width 20 mm, with adjustment, screw fixing, nickel-plated zinc alloy
- > Installation instructions
- > Order qty: 1 set



Anthracite colour cover caps are also available, shown on page **9.221**



Generally used on door width	For flap weight	No. of connecting hinges included	Grey
For 550 mm cabinet height			
600/800 mm	7.8 - 15.2 kg	2 pcs	372.38.000
For 720 mm cabinet height			
600 mm	6.1 - 10.8 kg	2 pcs	372.38.002
800/1000 mm	8.5 - 14.4 kg	3 pcs	372.38.004