




Duo Forte flap/lid stay




Forte version shown


- > Heavy version - min. installation depth 175 mm
- > Order fixing screws separately
- > Order qty: 1 pc



Installation as flap stay




Separate catch required




No separate catch required.
Space required for fitting
inside the cabinet when the
flap is being closed:
175 mm from front edge of cabinet

For edge distance 37 mm (A)



For edge distance 28 mm (A)



Flap height (mm)	Maximum flap weight (kg)			
	Function locking		Function braking	
Installation as lid stay				
For opening angle 75°	1 stay	2 stays	1 stay	2 stays
200	14.0	15.0	15.0	15.0
250	11.5	15.0	15.0	15.0
300	9.0	15.0	12.0	15.0
350	8.0	15.0	11.0	15.0
400	7.0	14.0	9.0	15.0
450	6.0	12.5	8.0	15.0
500	5.5	11.0	7.0	15.0
550	5.0	10.0	6.5	13.0
600	5.0	9.5	6.0	12.0
650	4.0	8.5	5.5	11.0
700	4.0	8.0	5.0	10.5
For opening angle 90°	1 stay	2 stays	1 stay	2 stays
200	12.0	15.0	15.0	15.0
250	9.5	15.0	12.0	15.0
300	8.0	15.0	10.0	15.0
350	7.0	13.5	9.0	15.0
400	6.0	12.0	8.0	15.0
450	5.0	11.0	7.0	14.0
500	5.0	9.5	6.0	12.0
550	4.0	8.5	5.5	11.0
600	4.0	8.0	5.0	10.0
650	3.5	7.0	5.0	9.5
700	3.0	7.0	4.0	9.0
For opening angle 110°	1 stay	2 stays	1 stay	2 stays
200	9.5	15.0	12.5	15.0
250	7.5	15.0	10.0	15.0
300	6.5	12.5	8.0	15.0
350	5.5	11.0	7.0	14.0
400	4.5	9.5	6.0	12.5
450	4.0	8.5	5.5	11.0
500	4.0	7.5	5.0	10.0
550	3.5	7.0	4.0	9.0
600	3.0	6.0	4.0	8.0
650	3.0	5.5	4.0	7.5
700	3.0	5.0	3.5	7.0
Installation as flap stay (use 2 fittings)				
For opening angle 90°	2 stays		2 stays	
300	15.0		15.0	
350	13.5		15.0	
400	12.0		15.0	
450	11.0		14.0	
500	9.5		12.0	
550	8.5		11.0	
600	8.0		10.0	



For wooden lids/lids with aluminium frame, frame width from 45 mm

For Hospa screws

Distance from edge	Nickel-plated
28 mm	373.66.631
37 mm	373.66.632

For Varianta screws

Distance from edge	Nickel-plated
37 mm	373.66.634

For lids with aluminium frame, frame width from 20 mm

For sheet metal screws

Distance from edge	Nickel-plated
37 mm	373.66.642