


HÄFELE METALLA 300 A MINI 95°

For small doors and narrow frames



- > Opening angle 95°
- > Screw fixing cup
- > Drilling depth hinge cup: 10 mm
- > Door to cabinet with slide-on arm system
- > For 12-22 mm door thickness
- > Side adjustment 2 mm, height adjustment 2 mm (via mounting plate), depth adjustment 2 mm
- > With Automatic closing spring
- > Steel cup and hinge arm, nickel-plated
- > Order fixing screws separately
- > Order qty: Multiples of 250 pcs

Häfele Metalla 300 A mini, full overlay, 95°



Overlay - coverage of the side end by door e mm									
7.5	8.5	9.5	10.5	11.5	12.5	13.5	14.5	15.5	
						3	4	5	-2
					3	4	5		0
				3	4	5			2
3	4	5							4


DBE distance to cup bore edge mm

Mounting plate height f mm



Cup fixing	Drilling pattern 38/7.5
For screw fixing	311.46.520

Häfele Metalla 300 A mini, half overlay, 95°



Overlay - coverage of the side end by door e mm									
-1.5	-0.5	0.5	1.5	2.5	3.5	4.5	5.5	6.5	
						3	4	5	-2
					3	4	5		0
				3	4	5			2
3	4	5							4

DBE distance to cup bore edge mm

Mounting plate height f mm



Cup fixing	Drilling pattern 38/7.5
For screw fixing	311.46.521

TCH TECHNOLOGY 2022, © Häfele U.K. Ltd 2022. Dimensional data not binding. We reserve the right to alter specifications without notice.