

9



-

Door thickness	Distance to cup E mm				
	3.0	4.0	5.0	6.0	7.0
16	0.3	0.3	0.3	0.3	0.3
18	0.4	0.4	0.4	0.5	0.5
20	0.9	0.9	0.9	0.8	1.8
22	1.9	1.6	1.5	1.4	1.3
24	4.8	3.8	2.8	2.3	2.2
26	7.2	6.2	5.2	4.2	3.5
Minimum gap F					

[illegible]

Door overlay mm							
13	14	15	16	17	18	19	
		3	4	5	6	7	0
3	4	5	6	7			2
Distance to cup E mm				Mounting plate distance mm			



GRASS
25
YEAR
WARRANT




Soft close	Screw fixing
Without	348.28.600

 MOUNTING PLATES
Pages 9.80-82

FIXING SCREWS
Pages 13.6-12

OPTIONAL ACCESSORIES
Pages 9.87-88, 9.126-137



- > For TIOMOS click on fixing hinges only
- > Hospa screw fixing
- > Two part plate with ± 2 mm height adjustment via worm screw
- > Nickel-plated steel
- > Order fixing screws separately
- > Order qty: 1 pc



A wider range of mounting plates are shown on pages **9.80-82**

Height	Hospa screw
0 mm	348.38.511