

TIOMOS TIPMATIC PLUS 110°, 125° MIRRO/M9/M0 HINGES

9

Furniture Hinges and Flap Fittings: Hinges



- > For handle-less applications
- > Ø 35 mm cup (excluding Mirro and M0)
- > For 110° opening angle door thickness up to 24 mm (for door thicknesses 24 mm and above, a trial fitting is recommended)
- > For Mirro 125° opening angle, glass thickness 3-8 mm
- > For M9 110° opening angle, door thicknesses from 12 mm up to max. 28 mm
- > For M0 125° opening angle, door thicknesses of 6-10 mm
- > With reverse spring opening mechanism
- > Screw fixing cup (excluding Mirro and M0)
- > Click on arm
- > Order fixing screws separately
- > Order qty: 1 pc

YOU
ALSO
NEED:

 **MOUNTING PLATES**
Pages 9.80-82

 **TIPMATIC PIN**
Pages 9.78-79

OPTIONAL ACCESSORIES
Pages 9.87-88, 9.126-127

Grass Tiomos Tipmatic Plus 110° concealed hinges



For full technical specification
details see pages **9.52-53**

With opening mechanism	Nickel-plated	Tiomos Night (anthracite)
Full overlay mounting	348.31.101	348.31.822
Half overlay/twin mounting	348.31.102	-
Inset mounting	348.31.103	-

Grass Tiomos Tipmatic Plus Mirro 125° concealed hinge



For full technical specification
details see pages **9.70-71**

	Nickel-plated
With opening mechanism	348.41.140

Grass Tiomos Tipmatic Plus M9 110° concealed hinge



- > For door thicknesses from 12 mm up to max. 28 mm



For full technical specification
details see pages **9.66-67**

	Nickel-plated
With opening mechanism	348.24.101

PAGE AMENDED
18.10.24/1