



TIOMOS TIPMATIC 95°/110°/120°/160° HINGES




Drilling pattern for cup fixing



Drilling pattern for screw fixing



For 95°/110°/120° hinges



For 160° hinges

- > For handle-less applications
- > Ø 35 mm cup
- > For 95° opening angle door thickness up to 36 mm (for door thicknesses 29 mm and above, a trial fitting is recommended)
- > For 110°/120° opening angle door thickness up to 24 mm (for door thicknesses 24 mm and above, a trial fitting is recommended)
- > For 160° opening angle door thickness up to 32 mm (for door thicknesses over 29 mm, a trial fitting is recommended)
- > Without spring
- > Screw fixing cup
- > Click on arm
- > Order fixing screws separately
- > Order qty: 1 pc


YOU
ALSO
NEED:

MOUNTING PLATES
Pages 9.80-82

TIPMATIC PIN
Pages 9.78-79

OPTIONAL ACCESSORIES
Pages 9.78-79, 9.87-88, 9.126-137

TIOMOS TIPMATIC 95°/110°/120° concealed hinges




Application example with 2 mm mounting plate shown - see table opposite for details

Door overlay mm							
13	14	15	16	17	18	19	
		3	4	5	6	7	0
3	4	5	6	7			2
Distance to cup E mm				Mounting plate distance mm			



Opening angle	95°	110°	120°
Without soft close	348.42.401	348.31.401	348.36.401

TIOMOS TIPMATIC 160° concealed hinges




Application example with 2 mm mounting plate shown - see table opposite for details

Door overlay mm										
13	14	15	16	17	18	19	20	21	22	
		3	4	5	6	7	8	9	10	0
3	4	5	6	7	8	9	10			2
Distance to cup E mm							Mounting plate distance mm			



Opening angle	160°
Without soft close	348.32.401

Cruciform mounting plate, 4 point fixing



- > For TIOMOS click on fixing hinges only
- > Hospa screw fixing
- > Two part plate with ± 2 mm height adjustment via worm screw
- > Nickel-plated steel
- > Order fixing screws separately
- > Order qty: 1 pc

**BEST
SELLER**



Height	0 mm	2 mm
Hospa screw	348.38.511	348.38.512



A wider range of mounting plates are shown on pages 9.80-82