



Loox5 plinth lights

Recess mounted, monochrome



Häfele Loox5 LED 3079



2400 K		120°
26 lx		250 mm
7 lx		500 mm
3 lx		750 mm
1.6 lx		1000 mm

- > Orientation light for residential and commercial spaces
- > Integrated motion and ambient light sensor
- > For recessed or surface mounting
- > High-quality stainless steel cover (brushed or black)

- | | |
|------------------------------|--|
| > Dimmable: | No |
| > Area of application: | Safety lighting in plinths of bathroom and bedroom furniture |
| > Housing material: | Stainless steel |
| > Housing colour/finish: | Silver-colored/black |
| > Diffuser material: | Plastic |
| > Diffuser colour/finish: | Opal white |
| > Dim. (Ø x H): | 54 x 17.8 mm |
| > Drill hole Ø: | 40 mm |
| > Number of LEDs: | 3 |
| > Service life: | L80/B10 30,000 h |
| > Sensor range: | 0 – 3,000 mm |
| > Colour rendering index Ra: | 90 |
| > Installation: | For Mounting in drilled hole |
| > Mounting location: | Plinth |
| > Cable length: | 2,000 mm |
| > Supplied with: | 1 light with connecting cable
2 bezels
1 surface-mount housing incl. fixings materials |

Colour control only via Häfele Connect Mesh 6-way distributor 850.00.045 and 2-way distributor 850.00.847
Please order separately, see pages ► 1.122 and 1.129

Installation reference
When using the 6-way distributor with switching function or Häfele Connect Mesh, please always connect this light with integrated switch to the 7th output port (continuous current) of the 6-way distributor. Connect switchable light to the 7th output port (continuous current) of the 6-way distributor.

5 24 V Loox5 24 V driver see page ► 1.137

Voltage	Number of	Colour	Wattage	Luminous flux	Luminous	Colour rendering index CRI		Cat. No.
V	LEDs	temperature	W	lm	efficacy	R _a	R ₉	
		K			lm/W			
5 24 V	Häfele Loox5 LED 3079							
	3	2400	0.3	4	13	>90	>60	833.76.002