

Loox5 drivers

24 V - Eco



Häfele Loox5 Eco driver constant voltage 24 V

1



EXTRA
SLIM

2



3



4



5



- > Universal voltage input
- > With switch input

- > Version: With overload protection
- > Area of application: For use with Loox5 or Loox5 compatible 24V lights
- > With switching function: Yes
- > Colour: Black
- > Degree of protection: IP20
- > Input voltage: 220–240 V~; 50–60 Hz
- > Output voltage: DC 24 V +/- 3 %
- > Number of connections: 20 / 40 W: 4 sockets for 24V lights
60 / 90 / 120 W: 6 sockets for 24V lights
1 socket for switch
1 socket for country-specific mains lead
- > Life time: >30,000 hours
- > Supplied with: 1 driver with mounting accessories

5 24 V	Output power W	Output current A	Standby power consumption W	Dim. (L x W x H) mm	Cat. No.
1	20	0.83	≤0.5	138 x 50 x 16	833.72.728
2	40	1.67	≤0.5	192 x 60 x 16	833.72.737
3	60	2.5	≤0.5	221 x 70 x 16	833.72.739
4	90	3.75	≤0.5	260 x 70 x 16	833.72.747
5	120	5	≤0.5	260 x 70 x 16	833.72.749



Ambient temperature –20 °C to +45 °C
Ensure that there is a sufficient air supply and circulation at the mounting location



Please use drivers with a life time of >50,000 h for permanent operation.

Maximum lead length from the driver to the device is 10 m.

Long cable lengths in combination with large loads (strip light lengths) can result in voltage losses in the cable.

These lead to visible loss of brightness in the lights.

Loox main leads, socket at cable: C7



833.89.000 UK



833.89.009 bare ended

- > Voltage: 250V
- > Material: Plastic
- > Colour: Black
- > Packing: 1 pc

Type		Length mm	Cat. No.
	UK moulded plug	2000	833.89.000
		5000	833.89.080
	Bare ended	2000	833.89.009