

1


- > HAWA Frontino 40 H FS
- > Flush sliding system suitable for ward-
robes or tall cabinets
- > Symmetrical door arrangement
- > Range:
 - Max. door weight **40 kg** per door
 - Max. door width **587-1194 mm**
 - Max. door height **2360 mm** (cabinet
2400 mm)
 - Door thickness **19 mm**
 - Installation depth **250 mm**,
bottom **175 mm**
- > Complete sets for 2 sliding doors
- > Distance from handle to door edge:
 - Handle height
 - > Handle height: Max. **30 mm**



HAWA Frontino 40, top hung for overlay doors with concealed running gear








[illegible]

Technical drawing of a mechanical part, likely a bracket or support, showing dimensions in millimeters. The part has a base plate with a central slot and a vertical support on the right. Dimensions include overall width (155 mm), base thickness (19 mm), slot width (44 mm), and various offsets and radii.



HAWA Frontino 40 complete fitting set

1













> Complete set for 2 doors includes:

- A Top track front, anodised aluminium
- B Top track back, aluminum, anodized
- C Guide track, screw fixing, aluminium, 2 pcs
- D Guide profile, plastic, 1 pc
- E Translation profile, anodised aluminium, 2 pcs
- F Guide fixation profile, aluminium, 2 pcs
- G Guide track, screw fixing, aluminium, 1 pc
- H Running gear, left and right, 1 pair
- I Adjustment lever unit, left and right, 1 pair
- J Guide unit, left and right, 1 pair
- K Guide, left and right, 1 pair
- L Guide, left and right, 1 pair
- M Front fixation with adjustment, plastic, left and right, 1 pair
- N Front fixation, plastic, 2 pcs
- O Top guide curve, left and right, plastic, 1 pair
- P Bottom guide curve, left and right, plastic, 1 pair
- Q Guide cover, plastic, 2 pcs
- R Stopper to guide track, 2 pcs

> Track stopper system with soft closing mechanism integrated in running equipment

Fixings and installation instructions included

> Order qty: 1 set



Model	For cabinet width	Cat. No.
S	1200-1799 mm	406.02.095
M	1800-2199 mm	406.02.096
L	2200-2400 mm	406.02.097