

HAWA-JUNIOR 40/GP SLIDING GLASS DOOR SYSTEM

Version of HAWA-Junior 40/GL system where headroom is limited. Suspension patch fitting units with decorative face plates. Normally recommended for residential or light duty commercial applications.

2

Sliding & Folding Door Systems For Architectural Applications: Sliding Interior Doors

> HAWA-Junior 40/GP

> Range:

Max. door weight **40 kg**



Glass thickness **8-12.7 mm** (toughened or laminated)

Max. door height **2200 mm**

- > Top of glass panel close to underside of top track
- > Height adjustment facility after installation, ± 3 mm
- > Choice of bottom control - either clear threshold or floor channel to provide added stability for wider doors



Satin stainless steel effect finish also available, please contact us for more information




Glass cut-out detail



Tracks and fitting sets must be ordered separately, shown below and on page **2.41**

HAWA-Junior 40 tracks




- > Pre-drilled for mounting screws
- > Two top tracks are mounted side by side for double or multiple doors
- > Silver anodised aluminium
- > Order qty: 1 pc



Top track side fixing profile is available, shown on page **2.56**

Length	2.0 m	3.0 m	3.5 m
Cat. No.	940.40.200	940.40.300	940.40.350

HAWA-Junior 40, 80, 120 and 160/GP bottom guiding accessories and patch assembly cover plates



- F Patch assembly cover plates
- > Set comprises 4 rounded plates, plastic
 - > Order qty: 1 set


- G Patch fitting
- > For clamping of bottom guide to glass panel
 - > Order qty: 1 set (2 sets required per panel)

- H Bottom guide
- > For fitting to patch fitting, to keep glass door panel aligned correctly, with nylon pilot
 - > Order qty: 1 pc (2 pcs required per panel)

- I Channel
- > Pre-drilled for countersunk screws, anodised aluminium
 - > Order qty: 1 pc



Cover plates F:
1 set per panel required if clear threshold bottom guiding is used
2 sets per panel required if bottom guide channel is used



Patch assembly cover plates		Cat. No.
Item F		
Satin chrome		940.40.027
Stainless steel		940.40.023
Patch fitting		
Item G		940.40.026 
Bottom guide		
Item H		940.40.035 
Channel		2.5 m 3.5 m
Item I		940.81.250 940.81.350



Alternative bottom guide control options also available, shown on page **2.39**;
For clear threshold where no floor channel is possible, or alternative continuous guiding where floor channel is permitted



Most of the products you will find in this catalogue are available within 24 hours. However, to be able to offer the breadth of range in our collection, a small number of products have a longer lead time that is typically around 14 days. Please call 0800 171 2909 for an accurate delivery date when you see this symbol.