

HÄFELE FOLD 100-U SYSTEM - APPLICATION EXAMPLE

All parts available to order separately - shown on pages 3.22-27.

Application examples

- > Project details:
- > Doors open **Outward**
- > Panel width **1000 mm**
- > Panel height **2500 mm**
- > Panel thickness **67 mm**
- > Finish **Satin**

Bill of materials	No. doors in suite		
	3 left, 0 right	5 left, 0 right	5 left, 5 right
943.32.831 Track, 3.0 m, anodised aluminium	-	2 pcs	-
943.32.732 Channel, 3.0 m, black polypropylene	-	2 pcs	-
943.32.842 Track, 4.0 m, anodised aluminium	1 pc	-	3 pcs
943.32.742 Channel, 4.0 m, black polypropylene	1 pc	-	3 pcs
943.32.792* Pivot assembly, mortice, satin	1 pc	1 pc	2 pcs
943.32.218* Intermediate hinge, satin	1 pc	1 pc	2 pcs
943.32.808* Intermediate hanger set, satin	1 pc	2 pcs	4 pcs
943.32.074 Hinge handle set, satin	-	1 pc	2 pcs
943.32.099 Hinge handle set offset outward opening, satin	1 pc	1 pc	2 pcs
943.32.087 Flush bolt lockable, 190 mm, satin	1 pcs	2 pcs	5 pcs
943.32.185 Flush bolt lockable, 600 mm, satin	1 pcs	2 pcs	5 pcs
943.32.065 Track seal, 10 mm brush height, 6.0 m	1 pc	1 pc	2 pcs
943.32.063 Door perimeter seal, 6.0 m	3 pcs	5 pcs	9 pcs
943.32.061 Frame perimeter seal, 15.0 m	1 pc	2 pcs	2 pcs
Non-mortice alternatives*			
943.32.790 Pivot assembly, satin	1 pc	1 pc	2 pcs
943.32.275 Intermediate hinge, satin	1 pc	1 pc	2 pcs
943.32.806 Intermediate hanger set, satin	1 pc	2 pcs	4 pcs

