

FESTOOL CONTURO KA 65 EDGE BANDER

The start of the perfect edge.



CONTURO KA 65 edge bander, 1200W



- > Easy, clean and efficient working progress and patented cartridge gluing system for quick colour changes
- > Precision glue application for a perfect join quality and maximum adhesion
- > Nozzle system that is easy to clean, machine housing does not heat up, allowing safe working progress
- > Adhesive melts according to requirements and does not boil, discolour or deteriorate
- > Easy to handle, perfect ergonomics, clear view of the workpiece
- > Perfect in a system - integrated in a complete system of accessories and consumable materials for achieving the perfect edge
- > For affixing wooden, plastic or laminated plastic edging to panel materials
- > Possible to attach edging to simple rectangular components or more complex free forms
- > Also as an addition to the machining centre, for affixing edging to complex free form and round elements
- > Suitable for mobile use, for rapidly reworking edges in situ
- > Suitable for stationary use and small batches, straight edges, free form elements and gluing inclined edges, angle from 0-47°
- > Technical data
 - Edge height: 18-65 mm
 - Edge thickness: 0.5-3.0 mm
 - Inner radius: >50 mm
 - Heating time: 8 min
 - Melting temperature: 100-210 °C
 - Feed speed: 2/4 m/min
 - Safety class: I
 - Weight: 7.9 kg
- > Edge bander supplied with:
 - Front handle and 4x natural EVA adhesive
- > Edge bander with edge trimming set supplied with:
 - Protective edging
 - 20x SickFix Brilliant 2 80 x 133 P320 abrasive sheets
 - Additional roll, HSK 80 x 133 H sanding block
 - Trimming device, Scraper
 - Base runner scratch protector with 3 x felt layers, Polishing felt
 - S 800 StixFix sanding cloth
 - MPA 5010 or polish
- > Both supplied in a Systainer SYS 4 T-loc

Item	Cat. No.	Order qty
Edge bander	004.02.352	1 pc
Edge bander with edge trimming set	002.22.001	1 set