

KBT700XE

Product family: Hood
 Subfamily: Decorative wall hood
 Aesthetics: Neutral
 Design: T flat
 Width category: 70-80cm
 Extraction: Expulsion
 Electronic control
 Material: Stainless steel
 Color: Stainless steel
 Type of steel: Brushed
 EAN code: 8017709286620
 Hood width: 70 cm



Aesthetics

Logo: Silk screen

Controls

Control setting: Electronic buttons

Programs / Functions

No. of speeds: 3
 Intensive speed
 24h air filter function
 Time-setting options: Automatic switch-off

Technical Features

No. of lights: 2
 Light type: LED
 Light Power: 1,3 W
 Light color temperature scale (°K): 3000 °K
 Free outlet maximum capacity: 610 m³/h
 Motor power: 230 W
 No. of filters: 3
 Anti-grease filters: Aluminium

Filter replacement indicator
 Vent outlet: 150 mm
 Minimum distance from ELECTRIC hob: 500 mm
 Minimum distance from GAS hob: 650 mm
 Non return valve

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	256	48
Speed 2	347	55
Speed 3	463	63
Intensive speed	688	72

Accessories Included

Tube reduction

Performance / Energy Label



Annual Efficiency Consumption (AEChood): 53.5 KWh/year
Energy efficiency class (EEC): A
Fluid Dynamic Efficiency (FDE): 29.2
Fluid Dynamic Efficiency class (FDEC): A
Lighting Efficiency (LE): 65.0
Lighting Efficiency Class (LEC): A
Grease Filtering Efficiency (GFE): 79.8 %
Grease Filtering Efficiency Class (GFEC): C
Air flow at minimum speed (Qmin): 256 m³/h
Air flow at maximum speed (Qmax): 463 m³/h
Air flow at boost speed (Qboost): 688 m³/h
Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 47 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 62 dB(A)
Airbourne acoustical A-weighted sound power emission at

boost speed (SPEboost): 71 dB(A)
Power consumption in stand-by mode (Ps): 0.24 W
Time increase factor (F): 0.9
Energy Efficiency Index per first cavity: 51.9
Measured air flow rate at best efficiency point (Qbep): 386 m³/h
Measured air pressure at best efficiency point (Qbep): 428 Pa
Measured electric power input at best efficiency point (Wbep): 157 W
Normal Power of the light system (WI): 3 W
Average illumination of the light on the cooking surface (Emiddle): 157
Sound power level at highest setting (Lwa): 72 dB(A)


Electrical Connection

Electrical connection rating: 230 W
Voltage: 220-240 V
Frequency (Hz): 50-60 Hz
Power supply cable length: 1500 mm


Accessories not included



KITCEKBT
Chimney extension, dimensions 261,5 * 260 * 830 mm suitable for T-shape hood KBT* & KBCT*, max hight 1380 mm
Stainless Steel



KITFCKBT
1 pcs di filtro a carboni attivi per i modelli di cappe KBT* / KBCT*



KITFCKBTR
1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 20 times. dimension 237,5(H)x245x10 mm

