

A Connecting bolt

- With M6 thread
- For direct screw-in installation in **Ø 8 mm** holes or for press-fit installation in **Ø 8 or Ø 10 mm** holes when used with dowels **B** to **D**
- Steel

Drilling distance B	33.5 mm
Bright	262.75.098
Galvanized	262.75.990


Order qty: Multiples of 100 pcs

B Glued in sleeve, M6 internal thread

- For **Ø 8 mm** hole
- With grooves for glue
- Plastic

Length	Outer Ø	Cat. No.
11 mm	8.5 mm	039.33.462

Order qty: Multiples of 100 pcs





C Glued in sleeve, M6 internal thread

- For **Ø 10 mm** hole
- With grooves for glue
- Natural coloured nylon

Length	Individual	Strip of 20
9 mm	039.33.364	-
11 mm	039.33.266	-
13 mm	039.33.060	039.34.067*

Order qty: Multiples of 100 pcs (= 5 strips*)




D Sleeve, ribbed, M6 internal thread

- For **Ø 10 mm** hole
- Press-fit installation
- White plastic

Length	Cat. No.
18 mm	262.76.700

Order qty: Multiples of 100 pcs



TCH 2013. © Häfele U.K. Ltd 2013. Dimensional data not binding. We reserve the right to alter specifications without notice.