


Twin wheel swivel castor, hooded, Ø 40 mm wheels, plate fixing



Photo shows version without brake



- > With 32 x 32 mm mounting plate
- > 20 x 20 mm screw hole distances
- > Matt black plastic
- > Order qty: 1 pc




Wheel Ø	Load capacity	Without brake	With brake
Ø 40 mm	35 kg	660.62.332	660.62.333

Twin wheel swivel castor, hooded, Ø 40 mm wheels, plate fixing



Photo shows version without brake



- > With 38 x 38 mm mounting plate
- > 25 x 25 mm screw hole distances
- > Matt black plastic
- > Order qty: 1 pc




Wheel Ø	Load capacity	Without brake	With brake
Ø 40 mm	35 kg	660.63.332	660.63.333

Twin wheel swivel castor, hooded, Ø 40 mm wheels, plate fixing



Photo shows version with brake




- > With 38 x 38 mm mounting plate
- > 27 x 27 mm screw hole distances
- > Matt black plastic
- > Order qty: 1 pc



Wheel Ø	Load capacity	Without brake	With brake
Ø 40 mm	35 kg	660.65.332	660.65.333

Swivel castor, special use, Ø 40 mm wheel, plate fixing



- > With 42 x 42 mm mounting plate
- > Galvanized steel housing, black plastic wheel
- > Order qty: 1 pc



Wheel Ø	Load capacity	Without brake
Ø 40 mm	35 kg	662.03.870

COMPONENTS, FIXINGS AND CONSUMABLES 2014, © Häfele U.K. Ltd 2014. Dimensional data not binding. We reserve the right to alter specifications without notice.