

# KBT1200XE

Product family: Hood  
 Subfamily: Decorative wall hood  
 Aesthetics: Neutral  
 Design: T flat  
 Width category: > 90cm  
 Extraction: Expulsion  
 Electronic control  
 Material: Stainless steel  
 Color: Stainless steel  
 Type of steel: Brushed  
 EAN code: 8017709286637  
 Hood width: 120 cm



## Aesthetics

---

Logo: Silk screen

## Controls

---

Control setting: Electronic buttons

## Programs / Functions

---

No. of speeds: 3  
 Intensive speed  
 24h air filter function  
 Time-setting options: Automatic switch-off

## Technical Features

---

No. of lights: 2  
 Light type: LED  
 Light Power: 1,3 W  
 Light color temperature scale (°K): 3000 °K  
 Free outlet maximum capacity: 610 m³/h  
 Motor power: 230 W  
 No. of filters: 3  
 Anti-grease filters: Aluminium

Filter replacement indicator  
 Vent outlet: 150 mm  
 Minimum distance from ELECTRIC hob: 650 mm  
 Minimum distance from GAS hob: 650 mm  
 Non return valve

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	251	48
Speed 2	345	56
Speed 3	454	62
Intensive speed	690	72

## Accessories Included

---

Tube reduction

## Performance / Energy Label

---

Annual Efficiency Consumption (AEChood): 54.8 KWh/year  
 Energy efficiency class (EEC): A  
 Fluid Dynamic Efficiency (FDE): 30.2  
 Fluid Dynamic Efficiency class (FDEC): A  
 Lighting Efficiency (LE): 58.8  
 Lighting Efficiency Class (LEC): A  
 Grease Filtering Efficiency (GFE): 79.6 %  
 Grease Filtering Efficiency Class (GFEC): C  
 Air flow at minimum speed (Qmin): 251 m<sup>3</sup>/h  
 Air flow at maximum speed (Qmax): 454 m<sup>3</sup>/h  
 Air flow at boost speed (Qboost): 690 m<sup>3</sup>/h  
 Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 47 dB(A)  
 Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 61 dB(A)  
 Airborne acoustical A-weighted sound power emission at

boost speed (SPEboost): 71 dB(A)  
 Power consumption in stand-by mode (Ps): 0.23 W  
 Time increase factor (F): 0.9  
 Energy Efficiency Index per first cavity: 52.1  
 Measured air flow rate at best efficiency point (Qbep): 387 m<sup>3</sup>/h  
 Measured air pressure at best efficiency point (Qbep): 452 Pa  
 Measured electric power input at best efficiency point (Wbep): 161 W  
 Normal Power of the light system (WI): 3 W  
 Average illumination of the light on the cooking surface (Emiddle): 153  
 Sound power level at highest setting (Lwa): 72 dB(A)


### Electrical Connection

Electrical connection rating: 230 W  
 Voltage: 220-240 V  
 Frequency (Hz): 50-60 Hz  
 Power supply cable length: 1500 mm

### Accessories not included



**KITCEKBT**  
 Chimney extension, dimensions 261,5 \* 260 \* 830 mm suitable for T-shape hood KBT\* & KBCT\*, max height 1380 mm  
 Stainless Steel



**KITFCKBT**  
 1 pcs di filtro a carboni attivi per i modelli di cappe KBT\* / KBCT\*



**KITFCKBTR**  
 1 pcs of Charcoal filter Regenerable\* suitable for all the KBT/KBCT models. \* It can be washed in the dishwasher up to 20 times. dimension 237,5(H)x245x10 mm

